



Vitality Eco 7 Sport

Microshift XLE 10-speed / Bosch Performance Line / 500Wh / Disc

Article	Inch	Frame size	Color
122220121	28"	Gents, 50 cm	blue matt
122220122	28"	Gents, 55 cm	blue matt
122220123	28"	Gents, 60 cm	blue matt
122220125	28"	Ladies, 45 cm	blue matt
122220126	28"	Ladies, 50 cm	blue matt
122220127	28"	Ladies, 55 cm	blue matt
122220130	28"	Wave, 45 cm	blue matt
122220131	28"	Wave, 50 cm	blue matt
122220132	28"	Wave, 55 cm	blue matt

Drive System

Motor

Bosch Performance Line, Gen.3

36 Volt, Mid-engine

Output power 250 Watt

Display

Purion

Battery

Bosch Frame battery fully integrated

Energy content: 500 Wh

Voltage: 36 Volt

Capacity: 13,4 Ah

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	Aluminum 6061, Bosch fully integrated
	Head set	Chin Haur, tapered 1 1/8" – 1,5" semi-integrated
	Fork	Suntour NEX
	Shifting System	Microshift XLE RD-M660M, 10-speed
	Derailleur	---
	Brakes	Tektro HD-M275 (front 180 mm / rear 160 mm)
	Headlight	Herrmans MR Go, 30 LUX
	Rear light	Trelock, LS 654, with brake light function
	Carrier	Racktime Stand-it, with spring flap
	Saddle	Selle Royal Essenza
	Seat post	Humpert Ergotec Atar, patent, 31,6 mm, 300 mm
	Pedals	Marwi SP-823
	Kickstand	Comp Flex, rear kickstand
	Chainguard	SKS Chainbow_E
	Mudguard	SKS, plastic
	Other	maximum weight allowed 140 kg
	Weight	26,4 kg
Cockpit	Stem	a-head, angle adjustable, aluminum 31,8mm
	Handlebars	Promax HB-3188, 640 mm
	Grips	Herrmans DD37, with clamp
	Shift lever	Microshift XLE SL-M850-R, 10-speed
	Brake lever	Tektro HD-M275
Wheels/Tires/Drivetrain	Tires	Schwalbe Citizen, 47-622, reflex
	Rims	Schürmann YAK19 Disc aluminum, 36 holes
	Spokes	2,0 mm, black
	Front Hub	Shimano HB-TX506, 36 holes
	Rear Hub	Shimano FH-TX506, 36 holes
	Sprocket	Microshift XLE CS-H103A, 10-speed, 11-40 teeth
	Chain	KMC E10 EPT
	Inner bearing	---
	Bottom bracket	Miranda aluminum, 170 mm, KMC chainring 38 teeth
	Gear ratio (f:r)	38 teeth : 11-42 teeth