



Vitality Eco 8

Shimano Nexus 5-speed coasterbrake / Bosch Performance Line / 500Wh / Disc

Article	Inch	Frame size	Color
122220201	28"	Gents, 50 cm	leaf green matt
122220202	28"	Gents, 55 cm	leaf green matt
122220203	28"	Gents, 60 cm	leaf green matt
122220210	28"	Wave, 45 cm	moss green matt
122220211	28"	Wave, 50 cm	moss green matt
122220212	28"	Wave, 55 cm	moss green matt

Drive System

Motor

Bosch Performance Line, Gen.3

36 Volt, Mid-engine

Output power 250 Watt Watt

Display

Intuvia

Battery

Bosch Frame battery fully integrated

Energy content: 500 Wh

Voltage: 36 Volt

Capacity: 13,4 Ah

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	Aluminum 6061, Bosch fully integrated
	Head set	Chin Haur, tapered 1 1/8" – 1,5" semi-integrated
	Fork	Suntour NEX
	Shifting System	Shimano Nexus 5-speed coasterbrake
	Derailleur	---
	Brakes	Shimano BR-MT200 (front 180 mm / rear 160 mm)
	Headlight	Herrmans MR Go, 30 LUX
	Rear light	Trelock, LS 654, with brake light function
	Carrier	Racktime, with spring flap
	Saddle	Selle Royal Essenza
	Seat post	Humpert Ergotec SP 5.0, patent, suspension, 31,6 mm, 350 mm
	Pedals	Marwi SP-823
	Kickstand	Comp Flex, rear kickstand
	Chainguard	SKS Chainbow_E
	Mudguard	SKS, plastic
	Other	maximum weight allowed 140 kg
	Weight	26,8 kg
Cockpit	Stem	Humpert Ergotec Octopus 50, angle adjustable
	Handlebars	Humpert Ergotec City Cruiser, aluminum, 635 mm
	Grips	Herrmans DD37, with clamp
	Shift lever	Shimano Nexus, Twist grip
	Brake lever	Shimano Altus, 3-finger Brake lever
Wheels/Tires/Drivetrain	Tires	Schwalbe Citizen, 47-622, reflex
	Rims	Schürmann YAK19 Disc aluminum, 36 holes
	Spokes	Niro 2,0 mm
	Front Hub	Shimano HB-TX505, Centerlock, 36 holes
	Rear Hub	Shimano Nexus 5-speed SG-C7002-5CD, Centerlock, 36 holes, coasterbrake
	Sprocket	Shimano CS-C7000, 30 teeth
	Chain	KMC Z1 EPT
	Inner bearing	---
	Bottom bracket	Miranda aluminum, 170 mm, KMC chainring 38 teeth
	Gear ratio (f:r)	38 teeth : 30 teeth