



Vitality Eco 6 Street

Microshift XLE 10-speed / Bosch Performance Line CX / 500Wh / Disc

Article	Inch	Frame size	Color
122220250	27,5"	Wave, 45 cm	ruby red matt
122220251	27,5"	Wave, 50 cm	ruby red matt
122220252	27,5"	Wave, 55 cm	ruby red matt

Drive System

Motor

Bosch Performance Line CX, Gen. 4
36 Volt, Mid-engine
Output power 250 Watt

Display

Intuvia

Battery

Bosch Frame battery semi-integrated
Energy content: 500 Wh
Voltage: 36 Volt
Capacity: 13,4 Ah

Technical changes and changes in equipment reserved, color deviations possible.

	General
Frame	Aluminum 6061, Bosch semi-integrated
Head set	Acros AZX-212, tapered
Fork	Suntour XCM-ATB, 100 mm travel with lockout-function
Shifting System	Microshift XLE RD-M61S, 10-speed
Derailleur	---
Brakes	Radius BH-M960 (front 180 mm / rear 160 mm)
Headlight	Spanninga X&O XE, 30 LUX
Rear light	Trelock, LS 654, with brake light function
Carrier	Racktime Stand-it, with spring flap
Saddle	Selle Royal Essenza
Seat post	Humpert Ergotec Atar, patent, 27,2 mm, 300 mm
Pedals	Marwi SP-823
Kickstand	Comp Flex, rear kickstand
Chainguard	SKS Chainbow_E
Mudguard	SKS, plastic
Other	maximum weight allowed 140 kg
Weight	23,9 kg
	Cockpit
Stem	Humpert Ergotec Octopus 50, angle adjustable
Handlebars	Promax HB-3188, 640 mm
Grips	Herrmans DD37, with clamp
Shift lever	Microshift XLE SL-M850-R, 10-speed
Brake lever	Radius BH-M960, 3-finger Brake lever
	Wheels/Tires/Drivetrain
Tires	Schwalbe Super Moto-X, 62-584, reflex
Rims	Schürmann YAK19 Disc aluminum, 36 holes
Spokes	2,0 mm, black
Front Hub	Joytech, 36 holes
Rear Hub	Joytech D762TSE, 36 holes
Sprocket	Microshift XLE CS-H100, 10-speed, 11-36 teeth
Chain	KMC E10 EPT
Inner bearing	---
Bottom bracket	Miranda aluminum, 170 mm, KMC chainring 38 teeth
Gear ratio (f:r)	38 teeth : 11-36 teeth