



Vitality Eco 10

Shimano Nexus 5-speed freewheel / Bosch Performance Line CX / 625Wh / Disc / Gates

Article	Inch	Frame size	Color
122320361	27.5"	Gents, 50 cm	green glossy
122320362	27.5"	Gents, 55 cm	green glossy
122320363	27.5"	Gents, 60 cm	green glossy
122320365	27.5"	Wave, 45 cm	red glossy
122320366	27.5"	Wave, 50 cm	red glossy
122320367	27.5"	Wave, 55 cm	red glossy

Drive System

Motor

Bosch Performance Line CX, BES3

36 Volt, mid-engine

Output power 250 Watt

Display

Intuvia 100

Battery

Bosch frame battery fully-integrated

Energy content: 625 Wh

Voltage: 36 Volt

Capacity: 16.7 Ah

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	Aluminium 6061, Bosch BES3, fully integrated
	Head set	Acros AZX-585, tapered
	Fork	Suntour Mobie25, 100 mm suspension travel with lockout function
	Shifting System	Shimano Nexus 5-speed freewheel
	Derailleur	---
	Brakes	Shimano BR-MT200 (front 180 mm / rear 180 mm)
	Headlight	Busch & Müller Lumotec IQ-XS Highbeam, with high beam, 150 / 100 LUX
	Rear light	Trelock, LS 654, with brake light function
	Carrier	Racktime kickstand-it, strutless, with spring flap
	Saddle	Selle Royal Essenza
	Seat post	Humpert Ergotec Atar, patent, 30.9 mm, 300 mm
	Pedals	Marwi SP-823, black
	Kickstand	Comp Flex, rear kickstand
	Chainguard	SKS Chainbow_E
	Mudguard	SKS 75R, plastic
	Other	max load 140 kg
	Weight	28.6 kg
Cockpit	Stem	Humpert Ergotec Octopus 50, angle adjustable
	Handlebars	Humpert Ergotec City Cruiser, 635 mm
	Grips	Ergon GP1, with clamp
	Shift lever	Shimano Nexus, twist grip
	Brake lever	Shimano Altus, 3-finger brake lever
Wheels/Tires/Drivetrain	Tires	Schwalbe Super Moto, 62-584
	Rims	Schürmann YAK 21 Disc Aluminium hollow section, 36 holes
	Spokes	2.0 mm, black
	Front Hub	Shimano Alivio HB-MT400, 15 x 100 mm, Centerlock, 36 holes
	Rear Hub	Shimano Nexus 5-speed SG-C7000-5D, Centerlock, 36 holes, freewheel
	Sprocket	Gates CDX belt pulley, 32 teeth
	Chain	Gates CDX-drive belt
	Inner bearing	---
	Bottom bracket	Miranda Aluminium, 170 mm, 46 teeth
	Gear ratio (f:r)	46 teeth : 32 teeth