



## SWYPE 4.0 FS

Sram XO1 Eagle 12-speed / Bosch Performance Line CX / 750Wh

Article	Inch	Frame size	Color
122320501	29 / 27.5"	Unisex, 39 cm	black glossy
122320502	29 / 27.5"	Unisex, 42 cm	black glossy
122320503	29 / 27.5"	Unisex, 45 cm	black glossy
122320504	29 / 27.5"	Unisex, 48 cm	black glossy

### Drive System

#### Motor

Bosch Performance Line CX, BES3

36 Volt, mid-engine

Output power 250 Watt

#### Display

Purion

#### Battery

Bosch frame battery fully-integrated

Energy content: 750 Wh

Voltage: 36 Volt

Capacity: 20.1 Ah

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	fully integrated, Aluminium 6061, Boost 12 x 148 mm, Travel 160 mm
	Head set	Acros AZF-668-ICR, tapered, with cable integration
	Fork	Fox 38 Performance 29 eOptimized, 160 mm suspension travel, 3 Position Micro Adjust
	Shifting System	Sram XO1 Eagle, 12-speed
	Derailleur	---
	Brakes	Magura MT7 4 pistons (front 220 mm / rear 203 mm)
	Headlight	---
	Rear light	---
	Carrier	---
	Saddle	Ergon SM10 e-MTB
	Seat post	Limotec A1, dropper with remote, 31.6 mm
	Pedals	Marwi SP-102 Flat Pedal, Aluminium, black
	Kickstand	---
	Chainguard	chain guide
	Mudguard	---
	Other	max load 120 kg, light cable already installed in the frame
	Weight	26,5 kg
Cockpit	Stem	Humpert Ergotec Bass, 45 mm, 31.8 mm, Level 6+
	Handlebars	Humpert Ergotec Low Riser Bar, 780 mm, 31.8 mm, Level 6+
	Grips	Ergon GA20, with clamp
	Shift lever	Sram GX Eagle, 12-speed, Single Click
	Brake lever	Magura MT7
Wheels/Tires/Drivetrain	Tires	Schwalbe Magic Mary 62-622 (front), Hans Dampf 65-584 (rear)
	Rims	Mavic E-Deemax, 29"front / 27.5" rear
	Spokes	E-Deemax
	Front Hub	Mavic E-Deemax, 15 x 110 mm, 6-holes
	Rear Hub	Mavic E-Deemax, 12 x 148 mm, 6-holes
	Sprocket	Sram XG-1275 Eagle, 12-speed, 10-52 teeth
	Chain	Sram Eagle
	Inner bearing	---
	Bottom bracket	Miranda Aluminium, 165 mm, Sram Eagle chain ring 34 teeth, Narrow Wide
	Gear ratio (f:r)	34 teeth : 10-52 teeth