



SWYPE 2.0 HT Equipped

Sram SX Eagle 12-speed / Bosch Performance Line CX / 625Wh

| Article | Inch | Frame size | Color |
|-----------|------|---------------|--------------|
| 122320531 | 29" | Unisex, 38 cm | black glossy |
| 122320532 | 29" | Unisex, 42 cm | black glossy |
| 122320533 | 29" | Unisex, 46 cm | black glossy |
| 122320534 | 29" | Unisex, 50 cm | black glossy |

Drive System

Motor

Bosch Performance Line CX, BES3

36 Volt, mid-engine

Output power 250 Watt

Display

Intuvia 100

Battery

Bosch frame battery fully-integrated

Energy content: 625 Wh

Voltage: 36 Volt

Capacity: 16.7 Ah

Technical changes and changes in equipment reserved, color deviations possible.

| General | Frame | Aluminium 6061, Bosch BES3 fully integrated, Boost 12 x 148 mm |
|---------|-------------------------|---|
| | Head set | Acros AZF-668-ICR, tapered, with cable integration |
| | Fork | Suntour XCM34, Boost, 120 mm suspension travel with lockout function |
| | Shifting System | Sram SX Eagle, 12-speed |
| | Derailleur | --- |
| | Brakes | Magura MT Trail Sport 4 pistons (front 203 mm / rear 203 mm) |
| | Headlight | Spanninga Axendo 40, 40 LUX |
| | Rear light | SKS, Infinity |
| | Carrier | SKS Infinity GT4, with spring flap |
| | Saddle | Selle Italia Vivo E-MTB |
| | Seat post | Promax aluminium, patent, 31,6 mm, 400 mm |
| | Pedals | Marwi SP-450 Flat Pedal, black |
| | Kickstand | Comp Flex, rear kickstand |
| | Chainguard | Herrmans chain guard |
| | Mudguard | SKS A65R, plastic |
| | Other | max load 120 kg |
| | Weight | 26.5 kg |
| | Stem | Promax DA-230, 80 mm, 31.8 mm, with headlight holder |
| | Handlebars | Promax Riser Bar HB-3188, 740 mm, 31.8 mm |
| | Grips | Ergon GA30, with clamp |
| | Shift lever | Sram SX Eagle, 12-speed, Single Click |
| | Brake lever | Magura MT Thirty |
| | Tires | Schwalbe Smart Sam, 57-622, reflex |
| | Rims | Schürmann Craft 35, 29", 32 holes |
| | Spokes | 2.0 mm, black |
| | Front Hub | Sonos, Boost, 15 x 110 mm, 32 holes, 6-holes |
| | Rear Hub | Sonos, Boost, 12 x 148 mm, 32 holes, 6-holes |
| | Sprocket | Sram PG-1210 Eagle, 12-speed, 11-50 teeth |
| | Chain | Sram Eagle |
| | Inner bearing | --- |
| | Bottom bracket | Miranda Aluminium, 170 mm, Sram Eagle chain ring 38 teeth, with chain guard |
| | Gear ratio (f:r) | 38 teeth : 11-50 teeth |

General

Cockpit

Wheels/Tires/Drivetrain