



## SWYPE 3.0 FS WMN

Sram GX 12-speed / Bosch Performance Line CX / 750Wh

Article	Inch	Frame size	Color
122320551	27.5"	Unisex, 39 cm	black glossy
122320552	27.5"	Unisex, 42 cm	black glossy
122320553	27.5"	Unisex, 45 cm	black glossy

### Drive System

#### Motor

Bosch Performance Line CX, BES3

36 Volt, mid-engine

Output power 250 Watt

#### Display

Purion

#### Battery

Bosch frame battery fully-integrated

Energy content: 750 Wh

Voltage: 36 Volt

Capacity: 20.1 Ah

Technical changes and changes in equipment reserved, color deviations possible.

Category	Component	Description
General	Frame	fully integrated, Aluminium 6061, Boost 12 x 148 mm, Travel 140 mm
	Head set	Acros AZF-668-ICR, tapered, with cable integration
	Fork	Rock Shox Pike, Boost, 140 mm suspension travel with lockout function
	Shifting System	Sram GX Eagle , 12-speed
	Derailleur	---
	Brakes	Magura MT5 4 pistons (front 203 mm / rear 203 mm)
	Headlight	N/V, N/V LUX
	Rear light	---
	Carrier	---
	Saddle	Ergon SFC30
	Seat post	Humpert Ergotec Atar, patent, 31.6 mm, 300 mm
	Pedals	Marwi SP-102 Flat Pedal, Aluminium, black
	Kickstand	---
	Chainguard	chain guide
	Mudguard	---
	Other	max load 120 kg
Weight	26.5 kg	
Cockpit	Stem	Humpert Ergotec Bass, 45 mm, 31.8 mm, Level 6+
	Handlebars	Humpert Ergotec Low Riser Bar, 740 mm, 31.8 mm, Level 6+
	Grips	Ergon GA30, with clamp
	Shift lever	Sram GX Eagle, 12-speed, Single Click
Brake lever	Magura MT5	
Wheels/Tires/Drivetrain	Tires	Schwalbe Hans Dampf Super Trail, 65-584 , Classic Skin
	Rims	Schürmann Craft 35 , 27.5", 32 holes
	Spokes	Niro 2.0 mm, black
	Front Hub	Sram MTH700, 15 x 110 mm, 32 holes, 6-holes
	Rear Hub	Sram MTH700, 12 x 148 mm, 32 holes, 6-holes
	Sprocket	Sram PG-1210 Eagle, 12-speed, 11-50 teeth
	Chain	Sram Eagle
	Inner bearing	---
Bottom bracket	Miranda Aluminium, 165 mm, FSA chain ring 34 teeth, Narrow Wide	
Gear ratio (f:r)	34 teeth : 11-50 teeth	